


# TÄTTINGEN®

## User manual



### How to install Tättingen®

- 1 Clear away stones, leaves, and branches from the drain and the surrounding area.
- 2 Place TÄTTINGEN® with the arrows aligned in the same direction as the holes in the drain cover.
- 3 Position TÄTTINGEN® so that both the drain cover and the drain frame are covered.
- 4 Press down the handle and turn it a quarter turn, release, and check that the locking handle has hooked onto the underside of the drain cover.
- 5 Alert the workshop manager and people in the vicinity of the spill site.

### Cleanup procedures

- 1 Use spill equipment such as absorbents to absorb the spill.
- 2 Dispose of saturated absorbents in bags. The absorbents should be handled according to the regulations for the liquid.
- 3 Clean and restore the spill area with, for example, granulate.
- 4 Document the incident.

#### Assembly

Attach the handle using the included pin at the locking bracket.

#### Maintenance instructions

After use, TÄTTINGEN® should be cleaned and sanitized using a suitable agent for the specific chemical spill. Avoid using solvents such as paint thinner or similar products, as these can damage the gasket.

#### Storage


Should be stored hanging by the handle, e.g., using our accessory item no: 5T-055.



**Tip!** Watch our instructional video.



Spillguide



**PK Produkter AB - Industriell miljösäkerhet**

Snickarvägen 1B, 132 38 SALTSJÖ-BOO

Tel 010-129 40 00 [info@pk-produkter.se](mailto:info@pk-produkter.se)

[www.pk-produkter.se](http://www.pk-produkter.se)