

DATASHEET

Compact systems ECO 750, **** electric, 4 m, hose holder

Order number: 8251



TECHNICAL DATA

External dimensions (l x w x h)	108 x 77 x 167 cm
Weight	95 kg
Use	stationary
Installation Location	indoor
Material	PE/steel
Coating	galvanised
Operating Voltage	230 V
Frequency	50 Hz
Battery Capacity	without
Pump Drive	pump
Max. Flow Rate	9 l/min (max.)
Dispensing Hose Length	4.00 m
Hose Diameter	DN 15
Stackable	no
Warranty in years	5

EQUIPMENT

Lid	no
Battery / charger	without
Hose Reel	no
Flow Meter Main Medium	without
Filter with Water Separator	no
Contents gauge	mechanical

Overfill Sensor	no
Bund Leak Indicator	visual
Tank Data Management	no
Tanker Coupling	fuel cap 2"
Heating	no
Forklift Pockets	yes
Crane Eyes	no

SUITABLE MEDIA

Oil

LOGISTICS

Units per pallet	1
------------------	---

APPROVAL

DIBt Approval	Z-40.21-288
---------------	-------------

ACCESSORIES




7390 - Suction pipe with tanker coupling for tank up to 1000l



7391 - Leakage warning device 230V, optical and acoustic



10275 - Ultrasonic level indicator



11452 - Overfill prevention complete, supply voltage 230 V, comprising: level sender

[Link to product](#)

